



ECN	REV	DESCRIPTION	DATE	APPROVED

1. 芯数/NO. of contacts

系列/Series	303A	304A	305A	306A	307B	308A	312A	314B	319A
孔位排列/Pin Number									
适配线缆/Conductor size	0.75mm ²	0.75mm ²	0.75mm ²	0.75mm ²	0.75mm ²	0.75mm ²	0.25mm ²	0.25mm ²	0.25mm ²
导体直径/Pin size	1.5mm	1.5mm	1.5mm	1.5mm	1.5mm	1.5mm	1.0mm	1.0mm	1.0mm
额定电流/Rated current	7A	6A	6A	5A	5A	5A	3A	3A	3A
额定电压/Rated voltage	250V	250V	250V	250V	125V	60V	60V	60V	60V

2. 编码原则/Part Number



3. 技术特性/Technical Characteristics

1. 寿命/Durability: >500 mate/unmate cycles
2. Pin接触电阻/ Pin Contact Resistance: ≤10 mΩ
3. 绝缘电阻/Insulation Resistance: ≥ 100 MΩ
4. 温度等级/Rated Temperature: -25° C, +80° C
5. 盐雾/Corrosion Resistance: Salt spray test, >48h
6. 防水等级/Waterproof: IP67

6	弹性垫圈/Gasket: 硅胶/Silicone rubber
5	尾螺帽/Collect Nut: 黄铜镀镍/Brass, Nickel plated
4	线夹/Collect: 锌合金镀镍/ Zinc Alloy, Nickel plated
3	外壳/Outer Shell: 黄铜镀镍/Brass, Nickel plated
2	母针芯/PIN: 磷铜镀金/Phosphor copper, G/F
1	绝缘体/Insulator: PA BLACK
序号ITEM	名称 & 规格/Name & Description

SHEET	DIMENSION	TOLERANCES ARE:		TITLE:
		DECIMALES	ANGLES	
1 OF 1	MM	X±	±	浮动式插头/Free Plug
DWG NO.	REV.	APPROVALS	DATE	PART NO. M16K1303AFLBG1DZ
M16K	A0	CHECKED:		REV. *
		CHECKED:		
		DRAWN: S.peng	07/05/2016	

LINCONN Linconn Elc Tech Co.,LTD